

hush.  
*acoustics*

# Rondus

Spec Document



Check the product page

*Quiet by Design*

# Rondus

The Rondus tile embodies “less is more” with smooth, continuous lines and open spacing that highlight its timeless simplicity

## PRODUCT SPECIFICATIONS

Composition	100% PET (Polyethylene Terephthalate); 60% recycled material
Thickness	12mm
Product Placement	Walls
NRC	0.65
Fire Rating	CAN/ULC-S102 Class A ASTM E84 Class A
Sustainability	100% Recyclable
Warranty	2 Year Limited



# Rondus

## GREENGUARD® GOLD CERTIFICATION

Hush Acoustics has achieved full GreenGuard® Gold sustainability certification, a mark of excellence that ensures our products meet strict standards for low chemical emissions, promoting healthier indoor air quality.

This recognition gives architects, designers, and consumers confidence in choosing Hush for environmentally responsible solutions. Beyond sustainability, Hush's felt products offer excellent sound-absorbing properties, making them ideal for creating quieter, more comfortable spaces.

## SUSTAINABILITY

Manufactured from 100% PET(60% recycled material), our felt products demonstrate our commitment to both environmental stewardship and functional design, contributing to a greener and quieter future. It comprising of flame-retardant fiber as new material ensuring ASTM E84 class A certification. The high strength of PET panels in comparison to its weight is the key to its superior energy efficiency.

## FUNGAL RESISTANT

Independently tested by EMSL Canada, Hush P.E.T. felt showed zero mold growth under ASTM C1338 laboratory conditions, confirming exceptional durability.

## WARRANTY

2 year limited warranty. See F.A.Q. page on our website for more information.

## COMPLIMENTARY DOCUMENTATION



Environmental  
Product Declaration



Felt  
Maintenance Guide



Flame  
Spread

See Resource Hub page on website for more documentation


## RONDUS

<i>mm</i>	<i>inches</i>
600 x 600	23.6 x 23.6
800 x 600	31.5 x 23.6
1200 x 900	35.4 x 47.2
1200 x 1200	47.2 x 47.2

\* Custom sizes available upon request

# Rondus

## NOISE REDUCTION COEFFICIENT COMPARISON



Frequency (Hz)	No Cavity	50mm Cavity	100mm Cavity	ACT-grid 400mm
100	0.01	0.20	0.36	0.95
125	0.04	0.19	0.43	0.91
160	0.04	0.24	0.56	0.84
200	0.06	0.34	0.77	0.96
250	0.05	0.43	0.80	1.02
315	0.11	0.62	1	0.96
400	0.13	0.71	1.09	0.88
500	0.22	0.89	1.11	0.73
630	0.30	0.97	1.07	0.86
800	0.45	0.96	1.06	0.90
1000	0.57	0.99	1.08	0.90
1250	0.68	1.02	0.98	0.98
1600	0.76	0.99	0.86	1.02
2000	0.84	1	0.94	1.01
2500	0.93	0.97	1.04	1.04
3150	1	0.93	0.98	1.04
4000	1.03	1.03	1.03	1.02

Full NRC comparison available upon request

\*Tested panels laid parallel to the test surface.

\*\*Tested panels placed on the D50 frame, 304.8mm [12"] on centers spacing, laid parallel to the test surface. Perimeter edges were sealed with metal framing.


\*\*\*Tested panels butted together within the E400 Test Box. Perimeter edges were sealed with Duct Tape to the test box perimeter.

	No Cavity	50mm Cavity	100mm Cavity	ACT-grid 400mm
NRC	0.4	0.85	1	0.9

# Rondus


## HOW TO SPECIFY

### 1. Select Design



### 2. Select Size

See [page 3](#) for full size chart




### 3. Select Colour



Element



Luxe Series



Wood Grains




Concrete & Stone Grains

# Rondus


Prior to installation, installers are advised to unpack and lay out panels to determine the most aesthetically pleasing arrangement.

## INSTALLATION INSTRUCTIONS


1. Locate the back of the Wall Tile.  
*(Note; the back of the tile will have no etched patterns or beveled edges).*




2. On the back of the Wall Tile, starting at the top corner, apply a bead of adhesive that is approximately 1/4" wide.




3. Continue the bead of adhesive across the width of the Wall Tile.




4. Working quickly, complete the Wall Tile in a back-and-forth pattern as shown below.



5. Your Wall Tile is now ready to be installed on the wall in the desired location.  
*(Please note that the Wall Tile should be mounted on the wall within 60 seconds of applying adhesive).*



6. With the Wall Tile located on the wall, apply firm pressure evenly over the entire surface of the Wall Tile and hold it in place for 30 seconds. The Wall Tile is now installed. Repeat steps 1-6 for all remaining tiles.



# Colour Options

PLEASE NOTE: The images are only a sampling of the colours. Order a physical colour sample to obtain an accurate representation of our acoustic colours.


## ELEMENT



SUNFLOWER   APRICOT   WINE   CHERRY   TAMARIND   SALMON



GOLD   CARAMEL   CINNAMON   PEARL   MAPLE   MOCHA



MOSS   FORREST   CRYSTAL   AQUAMARINE   LAPIS   OCEAN



LAKE   ICE   LILAC   CHARCOAL   SLATE   OYSTER




SHADOW   CASPER   FOG   SNOW   VANILLA

## WOOD GRAINS




HONEY PINE   SAND




ANTIQUÉ OAK   CHERRY



WALNUT   MAHOGANY



BLACK TEAK   ASHWOOD



GREY MAPLE   WHITEMIST

# Colour Options (cont.)

PLEASE NOTE: The images are only a sampling of the colours. Order a physical colour sample to obtain an accurate representation of our acoustic colours.


## LUXE SERIES




# Colour Options (cont.)

PLEASE NOTE: The images are only a sampling of the colours. Order a physical colour sample to obtain an accurate representation of our acoustic colours.

## CONCRETE & STONE GRAINS



CONCRETE




TERRAZZO GREY




BRECCIA MARBLE



TERRAZZO ORANGE




PANDA MARBLE




BLACK MARBLE



BLACK AND GOLD GRANITE



GRUNGE MARBLE



GREEN QUARTZ



BLUE GRANITE

## COLOUR MATCH SERVICES

### Can't find the tone you're looking for?

Hush Acoustics' felt Colour Match services enhance architectural projects with rich visuals and tactile appeal, whether for panels, murals, or other design applications. Our felt brings depth and sophistication to any space, offering a customizable and memorable design element that elevates the overall experience.

With advanced equipment, we produce high-resolution, colour-accurate results that capture subtle gradients and fine textures, all while maintaining acoustic performance. Every Colour Match is carefully managed by our Senior Graphic Designer to ensure that the final output closely aligns with the designer's original vision.

### Commonly Matched Materials (matte finishes only):

#### Wall Paints

Dulux, Benjamin Moore, Behr, and other popular brands

#### Fabric

From linen to wool, we match not just the colour, but also the texture in most of the cases

#### Wood Laminates

WilsonArt and other popular brands

#### Pantone® Hues

We simulate your company's brand tones using the Pantone® Uncoated palette

#### Stones

We can simulate a wide variety of stone types based on your needs

#### Generic Textures

Get in touch with our Acoustic Specialists, we will be glad to assist you

Learn More  
**COLOUR  
MATCH SERVICES**





Rondus · Mocha

# hush. *acoustics*

Tailored for Architects,  
Interior Designers, and  
General Contractors, we serve  
as a fast, expert, and reliable  
partner for all your project ideas.

## *Quiet by Design*



Proudly Made  
in North America



2 Year  
Limited Warranty



**GreenGuard Gold®  
Certified**  
All Hush products  
exceed GreenGuard  
Gold® indoor air  
quality standards



**Fungal Resistant  
Certified**  
EMSL Canada verified  
zero mold growth  
for Hush P.E.T. felt  
(ASTM C1338).

hello@hushacoustics.ca · 204.454.1950  
31 Limestone Bay, Stonewall, MB  
Canada · R0C 2Z0

Follow us on Instagram  
@hush.acoustics

**hushacoustics.ca**

